

## 2700G Series

### Fuel Gas Coalescer Filter Element

### Element Information

2700G

A

#### Media

Multiple layers of synthetic materials and microglass

#### Support Layer

Stainless steel wire mesh for mechanical integrity

#### End Cap Configuration

Double Open Ended

#### Gasket Material

Viton (Flat)

#### Efficiency

A =	0.5μ
B =	0.3μ
1 =	2μ
6 =	0.3μ
7 =	0.5μ
9 =	5μ

#### Dimensions & Weight

	ID	OD	Length	Weight
A =	6-3/4"	10-1/4"	24-1/4"	24 lbs.
B =	11"	15-3/4"	24-5/8"	37 lbs.
1 =	6-7/8"	11-1/2"	28-1/2"	30 lbs.
6 =	16-3/4"	24-1/2"	36-1/4"	100 lbs.
7 =	4-1/4"	8-3/4"	20"	22 lbs.
9 =	6-3/4"	10-1/4"	24-1/4"	27 lbs.

#### Consult Factory



#### Construction

End Caps: Stainless Steel

Cores: Heavy gage stainless steel perforated sheet

#### Recommended Operating Conditions

Change out Differential Pressure: 15 PSID

Continuous Maximum Temp.: 400° F

Intermittent Maximum Temp.: 450° F